查询SY100E141供应商

FEATURES

- 700MHz min. shift frequency
- Extended 100E V_{EE} range of –4.2V to –5.5V
- 8 bits wide
- Bi-directional
- Four selectable modes for full functionality
- Asynchronous Master Reset
- Fully compatible with industry standard 10KH, 100K ECL levels
- Internal 75KΩ input pulldown resistors
- Fully compatible with Motorola MC10E/100E141
- Pin-compatible with E241
- Available in 28-pin PLCC package

DESCRIPTION

The SY10/100E141 are 8-bit, full-function shift registers designed for use in new, high-performance ECL systems. The E141 performs serial/parallel in and serial/parallel out, shifting in either direction. The eight inputs D_0–D_7 accept parallel input data, while DL/DR accept serial input data for left/right shifting.

The two select pins, SEL_0 and SEL_1 permit four modes of operation: Load, Hold, Shift Left and Shift Right, as shown in the Truth Table. Input data is clocked into the register on the rising clock edge after meeting the minimum set-up time. A logic HIGH on the Master Reset (MR) pin asynchronously resets all the registers to zero.

BLOCK DIAGRAM



PIN CONFIGURATION



PIN NAMES

Pin	Function
D_0-D_7	Parallel Data Inputs
DL, DR	Serial Data Inputs
SEL_0, SEL_1	Mode Select Inputs
CLK	Clock
Q_0-Q_7	Data Outputs
MR	Master Reset
V_{CCO}	V_{CC} to Output

TRUTH TABLE

Function	DL	DR	SEL_0	SEL_1	MR	CLK	Q_0	Q_1	Q_2	Q_3	Q_4	Q_5	Q_6	Q_7
Load	X	X	L	L	L	Z	D_0	D_1	D_2	D_3	D_4	D_5	D_6	D_7
Shift Right	X	L	L	H	L	Z	L	Q_0	Q_1	Q_2	Q_3	Q_4	Q_5	Q_6
	X	H	L	H	L	Z	H	L	Q_0	Q_1	Q_2	Q_3	Q_4	Q_5
Shift Left	L	X	H	L	L	Z	L	Q_0	Q_1	Q_2	Q_3	Q_4	Q_5	L
	H	X	H	L	L	Z	Q_0	Q_1	Q_2	Q_3	Q_4	Q_5	L	H
Hold	X	X	H	H	L	Z	Q_0	Q_1	Q_2	Q_3	Q_4	Q_5	L	H
	X	X	H	H	L	Z	Q_0	Q_1	Q_2	Q_3	Q_4	Q_5	L	H
Reset	X	X	X	X	H	X	L	L	L	L	L	L	L	L

DC ELECTRICAL CHARACTERISTICS

V_{EE} = V_{EE} (Min.) to V_{EE} (Max.); V_{CC} = V_{CCO} = GND

Symbol	Parameter	T_A = 0°C			T_A = +25°C			T_A = +85°C			Unit	Condition
		Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.		
I_{IH}	Input HIGH Current	—	—	150	—	—	150	—	—	150	µA	—
I_{EE}	Power Supply Current										mA	—
	10E	—	131	157	—	131	157	—	131	157		
	100E	—	131	157	—	131	157	—	151	181		

AC ELECTRICAL CHARACTERISTICS

V_{EE} = V_{EE} (Min.) to V_{EE} (Max.); V_{CC} = V_{CCO} = GND

Symbol	Parameter	T_A = 0°C			T_A = +25°C			T_A = +85°C			Unit	Condition
		Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.		
f_{SHIFT}	Max. Shift Frequency	700	900	—	700	900	—	700	900	—	MHz	—
t_{PLH} t_{PHL}	Propagation Delay to Output CLK MR	 625 600	 750 725	 975 975	 625 600	 750 725	 975 975	 625 600	 750 725	 975 975	ps	—
t_S	Set-up Time D SEL_0 SEL_1	 175 350 300	 25 200 150	 — — —	 175 350 300	 25 200 150	 — — —	 175 350 300	 25 200 150	 — — —	ps	—
t_H	Hold Time D SEL_0 SEL_1	 200 100 100	 –25 –200 –150	 — — —	 200 100 100	 –25 –200 –150	 — — —	 200 100 100	 –25 –200 –150	 — — —	ps	—
t_{RR}	Reset Recovery Time	900	700	—	900	700	—	900	700	—	ps	—
t_{PW}	Minimum Pulse Width CLK, MR	400	—	—	400	—	—	400	—	—	ps	—
t_{skew}	Within-Device Skew	—	60	—	—	60	—	—	60	—	ps	1
t_r t_f	Rise/Fall Time 20% to 80%	300	525	800	300	525	800	300	525	800	ps	—

NOTE:

1. Within-device skew is defined as identical transitions on similar paths through a device.

PRODUCT ORDERING CODE

Ordering Code	Package Type	Operating Range
SY10E141JC	J28-1	Commercial
SY10E141JCTR	J28-1	Commercial
SY100E141JC	J28-1	Commercial
SY100E141JCTR	J28-1	Commercial

28 LEAD PLCC (J28-1)



NOTES:
1. DIMENSIONS ARE IN INCHES[MM].
2. CONTROLLING DIMENSION: INCHES.
3. DIMENSION DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS, EITHER OF WHICH SHALL NOT EXCEED 0.008[0.203].
4. LEAD DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.
5. MAXIMUM AND MINIMUM SPECIFICATIONS ARE INDICATED AS FOLLOWS: MAX/MIN
6. PACKAGE TOP DIMENSION MAY BE SLIGHTLY SMALLER THAN BOTTOM DIMENSION.

Rev. 03

MICREL-SYNERGY 3250 SCOTT BOULEVARD SANTA CLARA CA 95054 USA

TEL + 1 (408) 980-9191 FAX + 1 (408) 914-7878 WEB http://www.micrel.com

This information is believed to be accurate and reliable, however no responsibility is assumed by Micrel for its use nor for any infringement of patents or other rights of third parties resulting from its use. No license is granted by implication or otherwise under any patent or patent right of Micrel Inc.

© 2000 Micrel Incorporated